



X-2000V 203 dpi
X-2300ZE 203 dpi



Industrial Label Printer | X-Series



Trusted Dependability, Quality Assured, Exceptional Value

Streamlined Features

- Excellent Value Industrial Tabletop
- Competitive Emulations
- CSI/CSO Ribbon Selection
- Integrated Communication Interfaces
- Adjustable Sensor

Industry Verticals

- Healthcare
- Retail
- Transportation & Logistics
- Tradeshow Management
- Automotive
- Manufacturing

Industry Applications

- Specimen Labeling
- Work in Process
- Parts Marking
- Product Labeling
- Compliance Labeling
- Shipping/Receiving
- Logistics Labeling

www.satoamerica.com/value

PRINTER MODEL		X-2000V	X-2300ZE
PRINT SPECIFICATIONS			
Printing Method		Direct Thermal/Thermal Transfer	
Print Resolution		203 dpi (8 dots/mm)	
Printing Speed		Up to 6 ips (152mm/s)	
Max. Print Area		4.09" (104mm) W x 50" (1270mm) L	4.09" (104mm) W x 100" (2540mm) L
MEDIA SPECIFICATIONS			
Sensor Type		Gap & I-mark	
Media Type		Roll and Fanfold	
Media Size	Width	1" to 4.4" (25.4mm to 112mm)	
	Thickness	0.0025" - 0.01" (0.0635 - 0.254mm)	
	Roll Specs	Maximum O.D.: 8" (203mm) / I.D.: 3" (76mm)	
Ribbon (TT only)		Width: 1" - 4", Max O.D.: 3" (76mm), Paper Core: 1" (25.4mm) CSI/CSO	
FONT/SYMBOLOGIES			
Internal Fonts		5 alpha-numeric fonts from 0.049" - 0.23" H (1.25mm - 6.0mm), expandable up to 24x24	
Barcode Symbologies	Linear	PPLA (only): Code 39, Code 93, Interleaved 2 of 5 (standard/with checksum digit/with human readable check digit), EAN-8, EAN-13, UPC-A, UPC-E, Postnet, Codabar, Code 128 subset A/B/C, UCC/EAN-128, UCC/EAN-128 K-MART, UCC/EAN-128, Random Weight, Plessey, HBIC, Telepen, FIM, UPC2, UPC5, GS1 Data Bar	PPLZ: Code 39 (standard/with check sum digit), Code 93 Interleaved 2 of 5 (standard/with checksum digit/with human readable check digit), EAN-8, EAN-13, UPC-A, UPC-E, Postnet, Codabar, Code 128 subset A/B/C, Code 128 Auto, UPC/EAN-Extension, Plessey, Industrial 2 of 5, Standard 2 of 5, Logmars, MSI, Code 11, GS1 DataBar
		PPLB: Code 39 (standard/with checksum digit), Code 93, Interleaved 2 of 5 (standard/with checksum digit/with human readable check digit), EAN-8, EAN-13, UPC-A, UPC-E, Postnet, Codabar, Code 128 subset A/B/C, Code 128 UCC (Shipping Container Code), Code 128 Auto, German, Postcode, Matrix 2 of 5, UCC/EAN 128, UPC Interleaved 2 of 5, GS1 Data Bar	
	PPLZ: Code 39 (standard/with checksum digit), Code 93, Interleaved 2 of 5 (standard/with checksum digit/with human readable check digit), EAN-8, EAN-13, UPC-A, UPC-E, Postnet, Codabar, Code 128 subset A/B/C, Code 128 Auto, UPC/EAN-Extension, Plessey, Industrial 2 of 5, Standard 2 of 5, Logmars, MSI, Code 11		
	2-D	PPLA/PPLB: MaxiCode, PDF417, Data Matrix, QR code, Composite codes PPLZ: MaxiCode, PDF417, Data Matrix, QR code	PPLZ: MaxiCode, PDF417, Data Matrix, QR code
COMMUNICATION INTERFACE			
Interface Options		Parallel, RS-232, USB, PS/2 keyboard	Parallel, RS-232, USB, PS/2 keyboard, Ethernet
MEMORY			
Memory		Flash ROM: 4MB, RAM: 8MB	Flash ROM: 8MB, RAM: 16MB
OPERATING CHARACTERISTICS			
Power Requirements		Autoswitching 100V~240VAC, Frequency: 50/60Hz, 5A	
Environment	Operating	40°~100°F (4°~38°C) / 10%~90% non-condensing	
	Storage	-4°~122°F (-20°~50°C)	
Regulatory Approvals		CE, FCC, cTUVus, CCC, RoHS	CE, FCC, UL, CUL, CCC, RoHS
Dimensions		9.84" (250mm) W x 16.45" (418mm) D x 10.35" (263mm) H	
Weight		24.25 lbs (11Kg)	
OPTIONS			
Printer Languages		PPLA/PPLB or PPLZ	PPLZ
Optional Accessories		Cutter, Dispenser, RTC Card, Rewinder	Cutter, Dispenser, Rewinder
Other Features		Printer Utility, Font Utility, Windows Driver	RTC standard, Printer Utility, Font Utility, Windows Driver

SATO AMERICA, INC.

CORPORATE
10350-A Nations Ford Rd
Charlotte, NC 28273
Phone: (704) 644-1650
Fax: (704) 644-1662
satosales@satoamerica.com

LABEL MANUFACTURING, SERVICE & SALES

NORTH AMERICA	BRAZIL	ARGENTINA
Illinois	Sao Paulo	Buenos Aires
Florida		
New Jersey		
North Carolina		

©2013 SATO America, Inc. All rights Reserved. Rev C • Specifications subject to change without notice • Any unauthorized reproduction of this content, in part or whole, is strictly prohibited • SATO is a registered trademark of SATO Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners.