

Printing Materials - Component

See General Information for Printing Materials - Component

ETIFLEX S.A. DE C.V.

MH64558

Av. Jesus Reyes Heróles 6

Col. San Pablo Xalpa

02980 Tlalnepantla, Mexico MEXICO

Pressure-sensitive systems:

Model Dsg.	Application Surface	Max Temp (°C)	Min Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
Unprinted stock dsg: MMFLCV1X Printed label dsg: MMFLCV1X Click here for suitable additional printing inks						
	Acrylic paint	150	-40	X	X	O, G
	Acrylic powder paint	150	-40	X	X	-
	Alkyd paint	150	-40	X	X	O, G
	Aluminum	150	-40	X	X	O, C, G
	Copper	150	-40	X	X	-
	Epoxy paint	150	-40	X	X	-
	Epoxy/Urethane powder paint	150	-40	X	X	O, G
	Galvanized steel	150	-40	X	X	O, C, G
	Glass	150	-40	X	X	-
	Polyester paint	150	-40	X	X	O, G
	Polyester powder paint	150	-40	X	X	O, C, G
	Polyurethane powder paint	150	-40	X	X	O, C, G
	Porcelain	150	-40	X	X	-
	Stainless steel	150	-40	X	X	O, C, G
	Epoxy powder paint	125	-40	X	X	O, C, G
	Melamine	100	-40	X	X	-
	Nylon - Polyamide	100	-40	X	X	O, G
	Phenolic - Phenol Formaldehyde	100	-40	X	X	-
	Polyurethane paint	100	-40	X	X	-

	Unsaturated polyester - thermoset	100	-40	X	X	-
	Acrylonitrile butadiene styrene	80	-40	X	X	O, G, C
	Chromate treated metal	80	-40	X	X	-
	Polybutylene terephthalate	80	-40	X	X	O
	Polycarbonate	80	-40	X	X	O, C
	Polyethylene	80	-40	X	X	-
	Polyethylene terephthalate	80	-40	X	X	-
	Polyphenylene oxide/ether	80	-40	X	X	-
	Polypropylene	80	-23	X	X	O, G, C
	Polystyrene	80	-40	X	X	O
	Polyvinyl chloride	80	-40	X	X	O

Unprinted stock dsg: **MMFLCV1X-CA**

Printed label dsg: **MMFLCV1X-CA**

[Click here for suitable additional printing inks](#)

	Acrylic paint	150	-40	X	X	O, G
	Acrylic powder paint	150	-40	X	X	-
	Alkyd paint	150	-40	X	X	O, G
	Aluminum	150	-40	X	X	O, C, G
	Copper	150	-40	X	X	-
	Epoxy paint	150	-40	X	X	-
	Epoxy/Urethane powder paint	150	-40	X	X	O, G
	Galvanized steel	150	-40	X	X	O, C, G
	Glass	150	-40	X	X	-
	Polyester paint	150	-40	X	X	O, G
	Polyester powder paint	150	-40	X	X	O, C, G
	Polyurethane powder paint	150	-40	X	X	O, C, G
	Porcelain	150	-40	X	X	-
	Stainless steel	150	-40	X	X	O, C, G
	Epoxy powder paint	125	-40	X	X	O, C, G
	Melamine	100	-40	X	X	-
	Nylon - Polyamide	100	-40	X	X	O, G
	Phenolic - Phenol Formaldehyde	100	-40	X	X	-

	Polyurethane paint	100	-40	X	X	-
	Unsaturated polyester - thermoset	100	-40	X	X	-
	Acrylonitrile butadiene styrene	80	-40	X	X	O, G, C
	Chromate treated metal	80	-40	X	X	-
	Polybutylene terephthalate	80	-40	X	X	O
	Polycarbonate	80	-40	X	X	O, C
	Polyethylene	80	-40	X	X	-
	Polyethylene terephthalate	80	-40	X	X	-
	Polyphenylene oxide/ether	80	-40	X	X	-
	Polypropylene	80	-23	X	X	O, G, C
	Polystyrene	80	-40	X	X	O
	Polyvinyl chloride	80	-40	X	X	O

Unprinted stock dsg: **MMFLCV4S**

[Click here for suitable additional printing inks](#)

	Acrylic paint	150	-40	X	X	O, G
	Alkyd paint	150	-40	X	X	O, G
	Aluminum	150	-40	X	X	O, C, G, DD, DL
	Copper	150	-40	X	X	-
	Epoxy paint	150	-40	X	X	-
	Epoxy/Urethane powder paint	150	-40	X	X	-
	Galvanized steel	150	-40	X	X	O, C
	Glass	150	-40	X	X	-
	Polyester paint	150	-40	X	X	O, G
	Polyester powder paint	150	-40	X	X	O, C
	Polyurethane powder paint	150	-40	X	X	O
	Porcelain	150	-40	X	X	O
	Stainless steel	150	-40	X	X	O, C
	Epoxy powder paint	125	-40	X	-	O, C
	Melamine	100	-40	X	X	O
	Nylon - Polyamide	100	-40	X	X	O, G
	Phenolic - Phenol Formaldehyde	100	-40	X	X	O

	Polycarbonate	100	-40	X	X	O, C
	Acrylonitrile butadiene styrene	80	-40	X	X	O, C, G
	Polybutylene terephthalate	80	-40	X	X	O
	Polyethylene	80	-40	X	X	-
	Polyphenylene oxide/ether	80	-40	X	X	-
	Polypropylene	80	-23	X	X	O, C, G
	Polystyrene	80	-40	X	X	O
	Polyvinyl chloride	80	-40	X	X	-
	Unsaturated polyester - thermoset	80	-40	X	X	O
Unprinted stock dsg: MMFLCV4X Click here for suitable additional printing inks						
	Acrylic paint	150	-23	X	X	C, O, G
	Alkyd paint	150	-23	X	X	C, O, G
	Aluminum	150	-40	X	X	C, O, G
	Copper	150	-40	X	X	-
	Epoxy powder paint	150	-40	X	X	C, O, G
	Galvanized steel	150	-23	X	X	C, O, G
	Glass	150	-23	X	X	C, O, G
	Polyester powder paint	150	-40	X	X	C, O, G
	Polyurethane powder paint	150	-40	X	X	C, O, G
	Porcelain	150	-23	X	X	C, O, G
	Stainless steel	150	-23	X	X	C, O, G
	Melamine	100	-23	X	X	C, O, G
	Phenolic - Phenol Formaldehyde	100	-23	X	X	C, O, G
	Acrylonitrile butadiene styrene	80	-23	X	X	C, O, G
	Polyphenylene oxide/ether	80	-23	X	-	C, O, G
	Polypropylene	80	-	X	-	C, O, G
	Polyvinyl chloride	80	-23	X	X	C, O, G

Note: Application surfaces are smooth, flat, and rigid unless otherwise specified. Labels suitable for application to two or more plastic or painted surfaces are considered suitable for blends of those plastics or paints, with Conditions of Acceptability common to the individual components in the blend.

C - Occasional exposure to Cooking Oil (room temp).

DL - Occasional exposure to Laundry Detergents.

DD - Occasional exposure to Dishwashing Detergents.

G - Occasional exposure to Gasoline splashing.

O - Occasional exposure to Lubricating Oil.

Note - (1) The following alternate nomenclature may be used: "BBS" or "BB Stainless", "C" or "Clear", "CM" or "Clear Matte", "G" or "Gold", "RBBS" or "RBB Stainless", "S" or "Silver", "SM" or "Silver Matte", "THRMFLM" or "THERMLfilm", "TMP" or "TMPRK" or "TAMPERmark", "W" or "White". (2) Additional characters may be added to the end of the label designation indicating the type of release liner used unless a specific release liner is indicated. (3) Model designations may or may not include hyphens, apostrophes, single quotes, or dashes as part of the nomenclature.

Marking: Company name, model designation and the Recognized Component Mark, .

Last Updated on 2020-12-08

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."